

body{font-family:Arial,sans-serif;margin:48px;line-height:1.45;color:#222}h1{color:#b3262d}h2{margin-top:24px;color:#333}small{color:#666}

Carpet Tile Collection Guide

Adapted from the authorized Fuxing Carpet paving guide: <https://www.carpettile.com.cn/fxywb/caseshow.asp?id=401>

Environmental requirements

Install carpet tiles on a dry, sound surface—not on walls or damp walls. A recommended environment is approximately 18–35°C, 15–60% relative humidity, and pH 5–9.

Prepare the substrate

Repair cracks, holes, and uneven areas. Clean the floor thoroughly and remove obstructions before setting out the installation.

Inspect materials

Check colour, quantity, quality, and transport damage before paving. Keep cartons dry, dust-free, flat, and stacked no higher than five boxes for long-term storage.

Tools and adhesive

Prepare cutters, scissors, rulers, tape, markers, chalk, a vacuum, spatula, pH test paper, humidity test paper, and a hot-air gun for careful repairs. Use suitable water-soluble environmental adhesive or double-sided adhesive where required.

Plan the layout

Draw the area to be carpeted and mark doors, windows, furniture, irregular corners, and seams in the lowest-traffic areas. Establish perpendicular chalk lines and check the right angle with the 3-4-5 method.

Lay the tiles

Follow the arrows printed on tile backs. Start at the centre cross and work outward in a step or pyramid sequence. Keep tiles tight, align edges and corners, and press each tile firmly into the adhesive.

Finish and inspect

Check the overall field after installation. Exchange unsuitable tiles and trim loose fibres carefully with scissors or a hot-air gun, avoiding damage to the carpet.